

Features


- Halogen free available upon request by adding suffix "-HF"
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings @ 25°C Unless Otherwise Specified

- Operating Junction Temperature Range: -65°C to +150°C
- Storage Temperature Range: -65°C to +150°C
- Maximum Thermal Resistance: 625°C/W Junction to Ambient (Note1)

Parameter	Symbol	Rating	Unit
Collector-Base Voltage BC846AW, BC846BW BC847AW, BC847BW, BC847CW BC848AW, BC848BW, BC848CW	V_{CBO}	80 50 30	V
Collector-Emitter Voltage BC846AW, BC846BW BC847AW, BC847BW, BC847CW BC848AW, BC848BW, BC848CW	V_{CEO}	65 45 30	V
Emitter-Base Voltage BC846AW, BC846BW BC847AW, BC847BW, BC847CW BC848AW, BC848BW, BC848CW	V_{EBO}	6 6 5	V
Collector Current	I_C	100	mA
Peak Collector Current	I_{CM}	200	mA
Peak Base Current	I_{BM}	200	mA
Power Dissipation	P_D	200	mW

Internal Structure




Marking:

BC846AW:1A; BC846BW:1B
BC847AW:1E; BC847BW:1F; BC847CW:1G
BC848AW:1J; BC848BW:1K; BC848C:1L


NPN General Purpose Transistors

SOT-323



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.071	0.087	1.80	2.20	
B	0.045	0.053	1.15	1.35	
C	0.083	0.096	2.10	2.45	
D	0.026		0.65		TYP.
E	0.047	0.055	1.20	1.40	
F	0.012	0.016	0.30	0.40	
G	0.000	0.004	0.00	0.10	
H	0.035	0.044	0.90	1.10	
J	0.002	0.010	0.05	0.25	
K	0.006	0.016	0.15	0.40	

Suggested Solder Pad Layout



Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Symbol	Min	Typ	Max	Units	Conditions
Collector-Base Breakdown Voltage BC846AW,BC846BW BC847AW,BC847BW,BC847CW BC848AW,BC848BW,BC848CW	$V_{(BR)CBO}$	80 50 30			V	$I_C=10\mu A, I_E=0$
Collector-Emitter Breakdown Voltage BC846AW,BC846BW BC847AW,BC847BW,BC847CW BC848AW,BC848BW,BC848CW	$V_{(BR)CEO}$	65 45 30			V	$I_C=10mA, I_B=0$
Emitter-Base Breakdown Voltage BC846AW,BC846BW BC847AW,BC847BW,BC847CW BC848AW,BC848BW,BC848CW	$V_{(BR)EBO}$	6 6 5			V	$I_E=1\mu A, I_C=0$
Collector-Base Cutoff Current	I_{CBO}			15	nA	$V_{CB}=30V, I_E=0$
				5	μA	$V_{CB}=30V, I_E=0, T_J=150^\circ C$
Emitter-Base Cutoff Current	I_{EBO}			100	nA	$V_{EB}=5V, I_C=0$
DC Current Gain BC846AW,BC847AW,BC848AW BC846BW,BC847BW,BC848CW BC847CW,BC848CW BC846AW,BC847AW,BC848AW BC846BW,BC847BW,BC848BW BC847CW,BC848CW	$h_{FE(1)}$		90 150 270			$V_{CE}=5V, I_C=10\mu A$
			110 200 420	180 290 520	220 450 800	$V_{CE}=5V, I_C=2mA$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		90	250	mV	$I_C=10mA, I_B=0.5mA$
			200	600	mV	$I_C=100mA, I_B=5mA$ (Note2)
Base-Emitter Saturation Voltage	$V_{BE(sat)}$		700		mV	$I_C=10mA, I_B=0.5mA$
			900		mV	$I_C=100mA, I_B=5mA$ (Note2)
Base-Emitter Voltage	V_{BE}	580	660	700	mV	$V_{CE}=5V, I_C=2mA$
				770	mV	$V_{CE}=5V, I_C=10mA$
Transition Frequency	f_T	100			MHz	$V_{CE}=5V, I_C=10mA, f=100MHz$
Collector Capacitance	C_C			4.5	pF	$V_{CB}=10V, I_E=I_C=0, f=1MHz$
Noise Figure	NF			10	dB	$V_{CE}=5V, I_C=200\mu A$ $R_S=2K\Omega, f=1KHz, BW=200Hz$

Notes: 1. Device Mounted on an FR4 Printed Circuit Board.

2. Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2.0\%$

Curve Characteristics

Fig. 1 - Static Characteristics




Fig. 2 - DC Current Gain Characteristics




Fig. 3 - Base-Emitter Saturation Voltage Characteristics




Fig. 4 - Collector-Emitter Saturation Voltage Characteristics




Fig. 5 - Base-Emitter Voltage Characteristics





Fig. 6 - Collector Power Derating Curve



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.