500ft Cat6 Bulk Unshielded (UTP) Ethernet Network Cable with Solid Conductors - Riser ...

In Stock

🛒 Add

★★★★★
5.0
| 2 Reviews
★★★★★
5.0
| 2 Reviews

💬 Need Help?

500ft Cat6 Bulk Unshielded (UTP) Ethernet Network Cable with Solid Conductors - Riser CMR-Rated - Blue

Create custom length in-wall, horizontal network cable runs

★★★★★
5.0
| 2 Reviews

Product # :   56015

🔍 Roll over image to zoom in

‹ ›

33 In Stock & ready to ship! ⓘ

1 ▲▼

🛒 Add

VISA MasterCard AMERICAN EXPRESS DISCOVER PayPal pay

Need it shipped today?
Place your order before the timer runs out!

⏱ 21:41:19

🖨 print   Y share   💬 chat

| 📇 Product Info | ⭐ Customer Reviews | 💬 Questions & Answers | 🌐 Distributors | ⋯ More Choices |

[Description] [Features] [Certifications] [Specs] [Uses]

Product Description

This riser rated Cat6 cable is perfect for creating custom length horizontal network cable runs. This cable offers an exceptional value for jobs that require standards compliance at a cost-effective price and meets all of the ANSI/TIA-568-C.2 specifications. It also offers other features that make it easier to use, save on installation time and expense, and ensure product quality during the installation. This cable features markings in feet and meters, which marks the exact amount of cable remaining in the box, and a wide opening for the payout design, which reduces tension on the wire as it is pulled during installation.

Product Features

• Riser, CMR-Rated jacket
• Meets ANSI/TIA-568-C.2 specification
• Foot and Meter marked to show the amount of cable left in the box
• Alpha numeric code printed every 2 feet for easy identification of cable runs

⚠ **WARNING:** Cancer and Reproductive Harm www.P65Warnings.ca.gov

Product Certifications

[TAA COMPLIANT]

Product Specifications

Color :	Blue
Length :	500.00 Foot

Jacket Rating :	Plenum
UPC :	757120560159
Warranty :	Lifetime
Vendor :	C2G
Weight :	11.680 LB

Pair Count: 4
Conductor: Solid annealed copper
Wire Gauge (mm): 23AWG (0.57mm)
Insulation: CMR Polyolefin
Insulation Colors:
• Pair 1: White/Blue, Blue
• Pair 2: White/Orange, Orange
• Pair 3: White/Green, Green
• Pair 4: White/Brown, Brown
Jacket: CMR Flame retardant (FR) PVC
Characteristic Impedance: 100 ± 15Ω
Nominal Velocity of Propagation: 70%
Performance Compliance:
• UL 444
• CSA C22.2 No. 214-08
• UL 1666
• NFPA 262
• ANSI/TIA-568-C.2
• ANSI/ICEA S-90-661-2012
• Article 800, NEC (NFPA 70)
• RoHS-compliant
NRTL Programs:
• UL Verified CAT 6
• UL, c(UL) Listed CMR
• UL, c(UL) Listed CMP
Sustainability:
• UL Certified EPD
• HPD
• USGBC Member
• RoHS2-compliant
• REACH-compliant

Product Uses

Ideal for:
• 10BASE-T through 1000BASE-T Ethernet
• Power over Ethernet (PoE) – IEEE 802.3af
• PoE+ – IEEE 802.3at Type 1 and 2
• ATM and token ring

Info	Service	Resources	Have A Question?
	Contact Us	Connector Guides	Get help with **Chat**

Order History

Where To Buy

More ⌄

OEM Solutions

Tech Support

More ⌄

ConnectXpress

Drivers & Manuals

More ⌄

Call C2G **800.506.9607**